





Ideal for High Precision Laboratory Research & Quality Control







DP-810 Data Printer

Sam	ple prir	t out
Start Da	:9	
25/04/	2018	17:03
1:	12.71	20 g
2:	11.6830 g	
3:	12.8090 g	
4:	12.9050 g	
5:	11.7730 g	
N:	5	1000
Avg:	12.3	760 g
S.dev:	0.5	970 g
R.dev:	4.82 %	
Min:	11.6830 g	
Max:	12.9050 g	
Diff:	1.2220 g	
Sum:	61.8	8820 g
25/04/2018		17:04
Signatu	re	

Accessories:

- DP-810 Data Printer
- HTDK-Density measurement kit

Tuning Fork Technology

External weight

Technical Specifications

220 g

0.0001 g

0.0001 g

0.0003 g

Ø 80 mm 213 x 290 x 314 mm (WxDxH)

mg, g, ct

AC-230V, 12V DC

RS-232C and peripheral device output

Tuning Fork frequency sensing Full weighing range


LCD with backlit

Weighing, counting, percentage, unit conversion density

Approx. 2.9 kg

Built-in weight

HT-224R



Sailent Features

- Password protection
- Shorter stabilization time
- Superior anti vibration filtering
- Dual Line LCD display
- Menu operation with function key
- HTR automatic and semi-automatic span adjustment with built-in calibration weight

Essae-Teraoka Pvt. Ltd.

Capacity

Readability

Repeatability

Linearity

Pan Size

Dimensions Weighing units

Power Source

Output

Measuring system

Tare

Calibration

Modes

Weight



Your Essae representative

DEEPAK ELECTRONICS

Adress - Near Railway Station, Sadhrana road, Garhi Harsaru, Gurgaon, Haryana - 122505

Mob No.- 9718298952, 9971589352

Email - deepakelectronics320@hmail.com

Form No.: CAT-HT-HTR-022 R12